


Plastic Injection Moulding, Plastic Blow Moulding, Auto Loader, Hopper Loader, Hopper Dryers, Flexographic Printing Machine, Rotogravure Printing Machine, Multi Colour Art Printing, (Offset Printing), Pet Preforms, Food and Pharma, Foot wear / Rubber/ Plastic processing & vacuum pumps



Wall Thick: 1.2mm to 2.5mm Temp. 90°C/125°C

**PU Hose Extra Heavy Duty**



Glass filled material conveyance  
Wall Thick: 4mm Temp. 100°C / 125°C

**PU Hose Super Heavy Duty**




Wall Thick: 0.6mm & 0.7mm Temp. 90°C / 125°C

**PU Hose Heavy Duty**




Powder Conveyance  
Wall Thick: 0.75 mm Temp. 80°C

**PU Hose with Rigid Helix  
(Food grade)**



Temp. 60°C


**PVC Non Toxic Hose  
with & without ANT copper Wire**



Size : 12 mm to 152 mm

Temp. 60°C / 70°C

**PVC Steel Wire Hose (Food Grade)**



Temp. 90°C

**Silicon Hose - Double Layer**



Hot Pet Conveyance

Wall Thick: 3mm Temp. 200°C

**Silicon Hose Super Heavy Duty FDA**



Temp. 135°C/150°C

**TPR Thermoplastic Rubber Hose**



Temp. 400°C to 1100°C

**Glass Fabric High. Temp. Hose**




Temp. 90°C / 125°C

**PU Hose Light Duty**



Temp. 60°C

**PVC Duct Hose Grey**



Temp. 60°C

**PVC Duct Hose Transparent**



Temp. 60°C


**Industrial Vacuum Cleaner Hose EVA  
(Swimming Pool Hose)**



Size : 6mm to 76 mm

Temp. 99°C

**PVC Braided Hose**



Temp. 60°C

**PVC Suction & Delivery Hose**