

Silicon Hose - Super Heavy Duty (FDA)

Inside Diameter (mm)	Outside Diameter (mm)	Bend. Radius (mm)	Pressure (bar)	Standard Length (m)
19	21.60	19	2.50	4
22	25.20	22	2.50	4
25	28.20	25	2.50	4
32	35.20	32	2.50	4
38	41.20	38	2.40	4
41	44.20	41	2.40	4
44	47.20	44	2.40	4
51	54.74	51	2.40	4
57	60.74	57	2.30	4
63	66.74	63	2.20	4
70	73.74	70	2.20	4
76	79.74	76	2.10	4
83	86.74	83	2.10	4
89	92.74	89	2.10	4
95	98.74	95	2.00	4
102	106.20	102	1.80	4
108	112.20	108	1.80	4
114	118.20	114	1.70	4
121	125.70	121	1.60	4
127	131.70	127	1.50	4
140	144.70	140	1.40	4
152	157.20	152	1.10	4
160	165.20	160	0.90	4
178	183.20	178	0.80	4
203	208.20	203	0.60	4
229	234.20	229	0.50	4
254	259.20	254	0.40	4
305	310.20	305	0.20	4

Other diameters: 26, 28, 40, 42, 45, 50, 52, 55, 58, 60, 62, 65, 67, 72, 80, 90, 91, 92, 100, 106, 110, 125, 130, 148, 150, 155, 156, 165, 180, 200, 210, 216.

Other Length spliced : 5-60 Coils.

All datas at ca.+23°C Dimensions between listed are possible on request.