

HIGH TEMPERATURE CLIP 650

Temp. - 60° C to + 650° C



Structure:

Very flexible ducting for temperatures up to + 650°C

Material:

2-ply, Silicone- coated high temperature fabric, reinforced by woven in stainless steel wire, silver-grey

Properties

Good temperature resistance, outer wear strip, flame retardant, excellent axial compressibility

Application




Suction of exhaust gases, flue gas extraction and suction of other hot fumes, gases or dust in all fields of industry

Temperature Resistance:

- 60° C to + 650° C

Standard Length:

3 to 10 meters
special lengths available.

				
int mm	kg/m	mm	mm	bar
50	0.60	0.75	30	0.44
60	0.70	0.75	36	0.31
65	0.80	0.75	39	0.26
70	0.90	0.75	42	0.23
76	1.00	0.75	45	0.2
80	1.00	0.75	48	0.17
83	1.20	0.75	54	0.14
102	1.30	0.75	60	0.11
112	1.30	0.75	66	0.09
120	1.40	0.75	72	0.08
127	1.40	0.75	75	0.07
140	1.60	0.75	84	0.06
152	1.80	0.75	90	0.05
160	1.80	0.75	96	0.04
180	2.10	0.75	108	0.04
203	2.80	0.75	120	0.03
254	3.20	0.75	175	0.02
305	4.35	0.75	210	0.01
407	6.40	0.75	280	0.01
508	8.20	0.75	400	0.01
600	9.10	0.75	500	0.01