

HIGH TEMPERATURE CLIP ARAMID

Temp. - 60° C to + 260° C



Structure:

Light weight and very flexible Silicone ducting

Material:

One-side Silicone-coated Aramid; fabric, inside: silver / outside: green

Properties

Good temperature resistance, outer wear strip, good resistance to mechanical influences and vibrations

Application

Suction of hot fumes, gases or dust in all fields of industry

Temperature Resistance:

- 60° C to + 260° C

Standard Length:

3 to 10 meters

					
int mm	kg/m	mm	mm	bar	bar
50	0.50	0.4	30.0	0.90	0.32
60	0.60	0.4	36.0	0.78	0.22
76	0.75	0.4	45.0	0.62	0.14
80	0.80	0.4	48.0	0.61	0.12
102	0.90	0.4	60.0	0.51	0.08
110	0.92	0.4	66.0	0.48	0.06
120	1.00	0.4	72.0	0.36	0.05
127	1.02	0.4	75.0	0.33	0.05
152	1.25	0.4	90.0	0.22	0.04
160	1.28	0.4	96.0	0.21	0.03
180	1.48	0.4	126.0	0.17	0.02
203	1.65	0.4	140.0	0.15	0.02
254	2.00	0.4	175.0	0.10	0.01
305	2.25	0.4	210.0	0.07	0.01
350	2.70	0.4	245.0	0.06	0.01
407	3.15	0.4	320.0	0.04	0.01
508	4.20	0.4	400.0	0.04	0.01